

Microcell Composite Company CELLOMER® 6000 SBS Rubber Pellets

Category : Polymer , Thermoplastic , Styrene-Butadiene , Styrene/Butadiene/Styrene (SBS)

Material Notes:

CELLOMER® PELLETS can be used in hot-pressing or with injection foaming boards. Featuring anti-slippage and elasticity. Information provided by Microcell Composite Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Microcell-Composite-Company-CELLOMER-6000-SBS-Rubber-Pellets.php

Physical Properties	Metric	English	Comments
Density	0.960 g/cc	0.0347 lb/in ³	
Melt Flow	22.8 g/10 min	22.8 g/10 min	
	@Load 5.00 kg, Temperature 200 Â°C	@Load 11.0 lb, Temperature 392 Â°F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	35	35	
Tensile Strength, Yield	58.8 MPa	8530 psi	
Elongation at Yield	400 %	400 %	
Tear Strength	11.8 kN/m	67.2 pli	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China