

Momentive Performance Materials 1200® Construction Sealant

Category : Polymer , Adhesive , Thermoset , Silicone , Silicone, RTV, Construction Grade

Material Notes:

One-part, premium glazing sealant for structural as well as general purpose glazing. Cure Method: Acetoxy. Tack-free time

Order this product through the following link:

http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-1200-Construction-Sealant.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	30	30	ASTM D2240
Tensile Strength, Ultimate	3.30 MPa	479 psi	ASTM D412
Tensile Strength, Yield	0.240 MPa	34.8 psi	at 50% Extension (0.5 x 0.38 x 2 in bead)

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 Â°C	399 Â°F	Elasticity is retained to this temperature.
Minimum Service Temperature, Air	-62.0 Â°C	-79.6 Â°F	Elasticity is retained to this temperature.

Processing Properties	Metric	English	Comments
Processing Temperature	27.0 Â°C	80.6 Â°F	Cure time to 0.38 in. is 5-7 days

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China