

Mytex Polymers AN16L-44 Polypropylene, Compounded

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Description: Compounded polypropylene produced for automotive exterior applications using Mytex® Technology. Key Applications: Body side molding
Information provided by Mytex Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Mytex-Polymers-AN16L-44-Polypropylene-Compounded.php

Physical Properties	Metric	English	Comments
Density	1.09 g/cc	0.0394 lb/in ³	ASTM D792
Melt Flow	18 g/10 min	18 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	16.0 MPa	2320 psi	50 mm/min; ISO 527
Flexural Modulus	1.55 GPa	225 ksi	Chord; 2 mm/min; ISO 178
Izod Impact, Notched (ISO)	25.0 kJ/m ² @Temperature 23.0 °C	11.9 ft-lb/in ² @Temperature 73.4 °F	ISO 180

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China