

Mytex Polymers AN16L-53 Polypropylene, Compounded

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Description: Compounded polypropylene produced for automotive exterior applications using Mytex® Technology. Key Applications: Body side molding
Information provided by Mytex Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Mytex-Polymers-AN16L-53-Polypropylene-Compounded.php

Physical Properties	Metric	English	Comments
Density	1.08 g/cc	0.0390 lb/in ³	ASTM D792
Melt Flow	13 g/10 min	13 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	20	20	ASTM D785
Tensile Strength, Yield	16.0 MPa	2320 psi	50 mm/min; ASTM D638
Flexural Modulus	1.15 GPa	167 ksi	Tangent; 1.3 mm/min; ASTM D790
Izod Impact, Notched	5.50 J/cm @Temperature 23.0 °C	10.3 ft-lb/in @Temperature 73.4 °F	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	70.0 °C	158 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China