

## **ND Industries 150 Wicking Adhesive High Pressure Sealant**

Category: Polymer, Adhesive, Thermoset

**Material Notes:** 

Seals pores in welds and hairline cracks in castings

Order this product through the following link:

http://www.lookpolymers.com/polymer\_ND-Industries-150-Wicking-Adhesive-High-Pressure-Sealant.php

Physical Properties	Metric	English	Comments
Viscosity	10 - 25 cP	10 - 25 cP	

Mechanical Properties	Metric	English	Comments
Shear Strength	>= 68.9 MPa	>= 10000 psi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	On steel (fixture)
	1440 min	24.0 hour	On Steel (Full)

Descriptive Properties	Value	Comments
Color	Green	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China