

ND Industries 150 Wicking Adhesive Sealant Threadlocker

Category : Polymer , Adhesive , Thermoset

Material Notes:

General DescriptionMedium to high strength. Locks pre-assembled fasteners through capillary action and seals porosities in welds and hairline cracks in castings.Meets military spec MIL-S-46163 Type III Grade R

Order this product through the following link:

http://www.lookpolymers.com/polymer_ND-Industries-150-Wicking-Adhesive-Sealant-Threadlocker.php

Physical Properties	Metric	English	Comments
Viscosity	10 - 25 cP	10 - 25 cP	

Mechanical Properties	Metric	English	Comments
Impact Test	2.26 - 11.3 J	1.67 - 8.33 ft-lb	Break
	22.6 - 39.5 J	16.7 - 29.2 ft-lb	Prevail

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	On steel (fixture)
	1440 min	24.0 hour	On steel (Full)

Descriptive Properties	Value	Comments
Color	Green	
Gap Fill, in.	0.004	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China