

Nabaltec NABALOX® NO 713-10 RF Reactive Alumina

Category : Ceramic , Oxide , Aluminum Oxide , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

NABALOX® aluminum oxide has a number of advantages including low sintering temperaturewide sintering rangeflexible processinghigh sintered densities high wear and impact resistanceelectrical insulationhigh mechanical strengthhigh temperature propertiesdimensional accuracyoptimized chemical resistanceRefractory Industry, Engineering CeramicsInformation provided by Nabaltec.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nabaltec-NABALOX-NO-713-10-RF-Reactive-Alumina.php

Physical Properties	Metric	English	Comments
Bulk Density	0.950 g/cc	0.0343 lb/in³	
Grain Size	0.80 µm	0.80 µm	Median
Specific Surface Area	7.0 m²/g	7.0 m²/g	BET

Component Elements Properties	Metric	English	Comments
Al2O3	99.7 %	99.7 %	
Fe2O3	0.030 %	0.030 %	
MgO	0.080 %	0.080 %	Doped
Na2O	0.10 %	0.10 %	
SiO2	0.050 %	0.050 %	

Descriptive Properties	Value	Comments
a-Al2O3 Content %	95	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China