

Nitriflex NitriClean N-689 B NBR - Nitrile Rubber

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE)

Material Notes:

Good oil resistance with good compression set properties great for extruded artifacts with good mechanical properties and low mold fouling. Applications: hose tubes and cover stocks, profiles, calendared sheet for die cut gaskets. Information provided by Dax Resinas

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nitriflex-NitriClean-N-689-B-NBR-Nitrile-Rubber.php

| Physical Properties | Metric | English | Comments | |
|---------------------|---------------------|---------------------|-------------------------------------|--|
| Volatiles | 0.00 - 0.70 % | 0.00 - 0.70 % | Method B-003; ASTM D5668 | |
| Mooney Viscosity | 79 - 91 | 79 - 91 | MML1+4, Method B-002; ASTM D1646 | |
| | @Temperature 100 °C | @Temperature 212 °F | | |
| Ash | 0.00 - 0.75 % | 0.00 - 0.75 % | ASTM D5667 | |

| Descriptive Properties | Value | Comments |
|---------------------------------|-----------------------------|------------|
| Appearance | Light beige to medium brown | |
| Bound Acrylonitrile Content (%) | 32 - 35 | ASTM D3533 |
| Polymerization | Cold | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China