

## Nye Lubricants 123 (Nyoil) Oil

Category : Fluid , Lubricant , White Mineral Oil (WMO)

### Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Nye-Lubricants-123-Nyoil-Oil.php](http://www.lookpolymers.com/polymer_Nye-Lubricants-123-Nyoil-Oil.php)

| Physical Properties                  | Metric  | English | Comments                                |
|--------------------------------------|---------|---------|-----------------------------------------|
| Viscosity Measurement                | 106     | 106     | Viscosity Index of Base Oil; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F)  | 37 cSt  | 37 cSt  | Base Oil; ASTM D445                     |
| Kinematic Viscosity at 100°C (212°F) | 5.8 cSt | 5.8 cSt | Base Oil; ASTM D445                     |

| Thermal Properties               | Metric   | English  | Comments           |
|----------------------------------|----------|----------|--------------------|
| Maximum Service Temperature, Air | 100 °C   | 212 °F   | Recommended        |
| Minimum Service Temperature, Air | -20.0 °C | -4.00 °F | Recommended        |
| Pour Point                       | -32.0 °C | -25.6 °F | Base Oil; ASTM D97 |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Base Fluid Type        | WMO   |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China