

Nye Lubricants 761G Grease

Category : Fluid , Lubricant , Alkylated Naphthalene (AN) , Polyalphaolefin (PAO) , Urea Gellant

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-761G-Grease.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	138	138	Viscosity Index of Base Oil; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	193 cSt	193 cSt	Base Oil; ASTM D445
Kinematic Viscosity at 100°C (212°F)	22 cSt	22 cSt	Base Oil; ASTM D445
Evaporation Loss	0.86 %	0.86 %	24 hrs, 150C; ASTM D972

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	251	251	ASTM D217
Penetration P(60), 1/10 mm	295	295	ASTM D217
Oil Separation	0.79 %	0.79 %	24 hrs, 100C; FTM 719B, 321.2

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	175 °C	347 °F	Recommended
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	Recommended
Pour Point	-42.0 °C	-43.6 °F	Base Oil; ASTM D97

Descriptive Properties	Value	Comments
Base Fluid Type	PAO/AN	
Gellant Type	Polyurea	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China