

Nye Lubricants NC-346 Grease

Category : Fluid , Lubricant , Clay Gellant , Synthetic Ether Base

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-NC-346-Grease.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	151	151	Viscosity Index of Base Oil; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	452 cSt	452 cSt	Base Oil; ASTM D445
Kinematic Viscosity at 100°C (212°F)	44 cSt	44 cSt	Base Oil; ASTM D445
Evaporation Loss	3.2 %	3.2 %	24 hrs, 200C; ASTM D972

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	255	255	ASTM D217
Penetration P(60), 1/10 mm	280	280	ASTM D217
Oil Separation	2.3 %	2.3 %	24 hrs, 200C; FTM 719B, 321.2

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	175 °C	347 °F	Recommended
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Recommended
Pour Point	-35.0 °C	-31.0 °F	Base Oil; ASTM D97

Descriptive Properties	Value	Comments
Base Fluid Type	Ester(POE)	
Gellant Type	Clay	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China