

Overview of materials for ASA/AES, Unreinforced, Extruded/Molded

Category : Polymer , Thermoplastic , AES Polymer , ASA Polymer , ASA/AES, Unreinforced, Extruded/Molded

Material Notes:

This property data is a summary of similar materials in the MatWeb database for the category "ASA/AES, Unreinforced, Extruded/Molded". Each property range of values reported is minimum and maximum values of appropriate MatWeb entries. The comments report the average value, and number of data points used to calculate the average. The values are not necessarily typical of any specific grade, especially less common values and those that can be most affected by additives or processing methods.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Overview-of-materials-for-ASAAES-Unreinforced-ExtrudedMolded.php

Mechanical Properties	Metric	English	Comments
Izod Impact, Notched	0.530 - 0.530 J/cm	0.993 - 0.993 ft-lb/in	Average value: 0.530 J/cm Grade Count:1
	@Temperature -40.0 - - 40.0 °C	@Temperature -40.0 - - 40.0 °F	
	0.530 - 0.530 J/cm	0.993 - 0.993 ft-lb/in	Average value: 0.530 J/cm Grade Count:1
	@Thickness 3.17 - 3.17 mm	@Thickness 0.125 - 0.125 in	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China