

Pacific Sintered Materials FX-226-T Infiltrated Iron Powdered Metal

Category : Metal , Ferrous Metal

Material Notes:

Machines and plates well. Good in hydraulic applications. Moderate tolerance control. Equivalent MPIF Specification: FX-1000-25All information provided by Pacific Sintered Metals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Pacific-Sintered-Materials-FX-226-T-Infiltrated-Iron-Powdered-Metal.php

Physical Properties	Metric	English	Comments
Density	7.20 - 7.50 g/cc	0.260 - 0.271 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell B	65	65	
Tensile Strength, Ultimate	352 MPa	51000 psi	
Tensile Strength, Yield	221 MPa	32000 psi	
Elongation at Break	7.0 %	7.0 %	
Modulus of Elasticity	110 GPa	16000 ksi	
Flexural Strength	910 MPa	132000 psi	Transverse Rupture
Charpy Impact, Unnotched	33.9 J	25.0 ft-lb	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China