

Pacific Sintered Materials FX-232-T(HT) Infiltrated High Carbon Steel Powdered Metal

Category : Metal , Ferrous Metal , Carbon Steel , High Carbon Steel

Material Notes:

Good strength, shock resistance and hardenability. Moderate tolerance control. Equivalent MPIF Specification: FX-1008-110HT All information provided by Pacific Sintered Metals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Pacific-Sintered-Materials-FX-232-THT-Infiltrated-High-Carbon-Steel-Powdered-Metal.php

Physical Properties	Metric	English	Comments
Density	7.20 - 7.50 g/cc	0.260 - 0.271 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell B	43	43	
Tensile Strength, Ultimate	827 MPa	120000 psi	
Tensile Strength, Yield	827 MPa	120000 psi	
Elongation at Break	<= 0.50 %	<= 0.50 %	
Modulus of Elasticity	110 GPa	16000 ksi	
Flexural Strength	1300 MPa	189000 psi	Transverse Rupture
Charpy Impact, Unnotched	9.49 J	7.00 ft-lb	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China