

Plaskolite Optix® CA-82 UVA UV-Absorbing Acrylic Resin

Category : Polymer , Thermoplastic , Acrylic (PMMA) , Acrylic, UV Stabilized, Molded

Material Notes:

Special UV-absorption grade, extrusion and injection molding Applications: A special UV-absorption acrylic resin for injection molding and contains a mold release agent. This resin offers high heat resistance and excellent stiffness/strength properties Yellowness Index 0.6-1.4 per ASTM D1925.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Plaskolite-Optix-CA-82-UVA-UV-Absorbing-Acrylic-Resin.php

Physical Properties	Metric	English	Comments
Density	1.19 g/cc	0.0430 lb/in ³	ASTM D792
Melt Flow	2.6 g/10 min	2.6 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	67.6 MPa	9800 psi	ASTM D638

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	94.0 °C	201 °F	ASTM D648
Vicat Softening Point	102 °C	216 °F	Rate A, ASTM D1525

Optical Properties	Metric	English	Comments
Haze	3.0 %	3.0 %	ASTM D1003
Transmission, Visible	92 %	92 %	ASTM D1003

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China