

PolyOne Geon™ Vinyl Flexible D9002 Polyvinyl Chloride, Flexible (PVC, Flexible)

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Information provided by PolyOne

Order this product through the following link:
http://www.lookpolymers.com/polymer_PolyOne-Geon-Vinyl-Flexible-D9002-Polyvinyl-Chloride-Flexible-PVC-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.58 g/cc	1.58 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	83	83	15 sec; ASTM D2240
Tensile Strength at Break	8.96 MPa	1300 psi	Type IV, 510 mm/min; ASTM D638
Elongation at Break	200 %	200 %	Type IV, 510 mm/min; ASTM D638

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-18.9 °C	-2.02 °F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	177 - 179 °C	351 - 354 °F	
	193 - 204 °C	379 - 399 °F	

Descriptive Properties	Value	Comments
Features	Low Gloss	
Forms	Pellets	
Generic Material	PVC, Flexible	
Generic Name	Polyvinyl Chloride, Flexible (PVC, Flexible)	
Processing Method	Extrusion	
	Injection Molding	
Regional Availability	Africa & Middle East	
	Asia Pacific	
	Europe	

Descriptive Properties	North America Value	Comments
	South America	
Uses	Construction Applications	
	Cove Base	
	Stair Tread	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China