

Polymax® Maxelast® A9860 TPE, ABS/PC Overmold

Category : Polymer , Thermoplastic , Elastomer, TPE

Material Notes:

Polymax's TPE material complies with UL, VDE, FDA, RoHS and PAH's standards. Uses: Consumer Products Toys & Novelties Auto Parts Tool Hand Grips Sporting Goods Wire & Cable Electronics Medical Devices Information from Alliance Polymers & Services, Distributor of Nantong Elastomer Technology Co.Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Polymax-Maxelast-A9860-TPE-ABSPC-Overmold.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.15 g/cc	1.15 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60	60	ASTM D2240
	@Time 10.0 sec	@Time 0.00278 hour	
Tensile Stress	2.03 MPa	294 psi	ASTM D412
	@Strain 100 %	@Strain 100 %	
	3.24 MPa	470 psi	ASTM D412
	@Strain 300 %	@Strain 300 %	
Tensile Strength, Yield	8.00 MPa	1160 psi	ASTM D412
Elongation at Break	760 %	760 %	ASTM D412

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China