

Polymax® Maxelast® F7875 TPE, Fire Retardant

Category : Polymer , Thermoplastic , Elastomer, TPE

Material Notes:

Polymax's TPE material complies with UL, VDE, FDA, RoHS and PAH's standards. Uses: Auto Parts, Seals, Wire & Cable Electronics. Information from Alliance Polymers & Services, Distributor of Nantong Elastomer Technology Co. Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Polymax-Maxelast-F7875-TPE-Fire-Retardant.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.15 g/cc	1.15 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	ASTM D2240
	@Time 10.0 sec	@Time 0.00278 hour	
Tensile Stress	4.07 MPa	590 psi	ASTM D412
	@Strain 100 %	@Strain 100 %	
	5.85 MPa	848 psi	ASTM D412
	@Strain 300 %	@Strain 300 %	
Tensile Strength, Yield	7.45 MPa	1080 psi	ASTM D412
Elongation at Break	460 %	460 %	ASTM D412

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China