

Polyplastic Armoflen® PO MF 65-1 Linear Low Density Polyethylene, 65% Calcium Carbonate

Category : Polymer , Thermoplastic , Polyethylene (PE) , LLDPE , Linear Low Density Polyethylene (LLDPE), Blow Molding Grade , Linear Low Density Polyethylene (LLDPE), Sheeting Grade

Material Notes:

Information provided by PolyPlastic Group.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Polyplastic-Armoflen-PO-MF-65-1-Linear-Low-Density-Polyethylene-65-Calcium-Carbonate.php

Physical Properties	Metric	English	Comments
Density	1.64 - 1.65 g/cc	0.0592 - 0.0596 lb/in ³	ISO 1183
Particle Size	1.5 µm	1.5 µm	
Melt Flow	3.0 - 5.0 g/10 min @Load 5.00 kg, Temperature 190 °C	3.0 - 5.0 g/10 min @Load 11.0 lb, Temperature 374 °F	ISO 1133

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.10 %	<= 0.10 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China