

Polyram RamLloy PBB520 PC/ABS alloy, Flame Retardant

Category : Polymer , Thermoplastic , ABS Polymer , Polycarbonate/ABS Alloy, Unreinforced , Polycarbonate (PC)

Material Notes:

Flame retardant PC/ABS alloy for injection molding applicationsInformation provided by Polyram Ram On Ind.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Polyram-RamLloy-PBB520-PCABS-alloy-Flame-Retardant.php

Physical Properties	Metric	English	Comments
Density	1.13 g/cc	0.0408 lb/in ³	DIN 53479
Linear Mold Shrinkage	0.0050 - 0.0080 cm/cm	0.0050 - 0.0080 in/in	
Melt Flow	25 g/10 min @Load 5.00 kg, Temperature 240 °C	25 g/10 min @Load 11.0 lb, Temperature 464 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	50.0 MPa	7250 psi	ASTM-D638
Elongation at Break	25 %	25 %	ASTM-D638
Tensile Modulus	2.20 GPa	319 ksi	ASTM-D790
Izod Impact, Notched	3.50 J/cm @Temperature 23.0 °C	6.56 ft-lb/in @Temperature 73.4 °F	ASTM-D256

Thermal Properties	Metric	English	Comments
Glow Wire Test	960 °C	1760 °F	

Electrical Properties	Metric	English	Comments
Surface Resistance	1.00e+14 ohm	1.00e+14 ohm	DIN 53482
Dielectric Strength	24.0 kV/mm	610 kV/in	VDE 0303/4

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China