

Precision Polymer Engineering N90E Nitrile Rubber

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

High Nitrile Rubber, 85-95 °IRHD. High acrylonitrile (ACN) content. Copolymer of acrylonitrile and butadiene. ASTM designation = NBR. ISO designation = NBR. Aerospace Material Specification DTD5509 Grade A. (Inactive for new design). Applications: Synthetic rubber resistant to engine lubricating oils, greases and fuels.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Precision-Polymer-Engineering-N90E-Nitrile-Rubber.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	°IRHD; ASTM D1415
Tensile Strength, Yield	8.60 MPa	1250 psi	ASTM D412
Elongation at Break	50 %	50 %	ASTM D412
Compression Set	50 %	50 %	24 hours @ 120°C; ASTM D395

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	120 °C	248 °F	
Minimum Service Temperature, Air	-30.0 °C	-22.0 °F	
	-30.0 °C	-22.0 °F	Non-brittle after 3 minutes
Flash Point	>= 300 °C	>= 572 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China