

## **Precision Polymer Engineering S70U Silicone Rubber**

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE), Silicone

## **Material Notes:**

Black Silicone Rubber, 66-75 °IRHD. Silicone rubber having both methyl and vinyl substituent groups on the polymer chain. Specially formulated for anti-static, semi-conductive applications. ASTM & ISO designation = VMQ.Applications: Low compression set grade, offering excellent heat resistance and low temperature flexibility. Used primarily for dry heat static seals, low physical strength and poor abrasion resistance prevents dynamic sealing.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Precision-Polymer-Engineering-S70U-Silicone-Rubber.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70	70	°IRHD; ASTM D1415
Tensile Strength, Yield	4.80 MPa	696 psi	ASTM D412
Elongation at Break	200 %	200 %	ASTM D412
Compression Set	20 %	20 %	70 hours @ 150°C; ASTM D395

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	160 °C	320 °F	
Minimum Service Temperature, Air	-60.0 °C	-76.0 °F	Non-brittle after 3 minutes
	-50.0 °C	-58.0 °F	
Flash Point	>= 300 °C	>= 572 °F	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China