

Premix Thermoplastics PREADD SL 104

Category : Polymer , Thermoplastic

Material Notes:

PREADD SL 104 is a slip masterbatch developed for blown PE-LD films. PREADD SL 104 is based on highly purified erucamide neutral in odor and color. PREADD SL 104 does not give problems in printing, heat sealing or bonding if not overdosed. PREADD SL 104 is approved for use in contact with foodstuffs according to FDA regulations without limitations and according to BgVV regulations as long as the dosage of PREADD SL 104 is less than 8.3 %. Information provided by Premix Thermoplastics Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Premix-Thermoplastics-PREADD-SL-104.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	
Additive Loading	3.0 %	3.0 %	Erucamide

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.25 %	<= 0.25 %	When Produced
Shelf Life	12.0 Month	12.0 Month	Normal Storing Conditions

Descriptive Properties	Value	Comments
Appearance	Granule	
Carrier	PE-LLD	
Color	Transparent	
Dosing, %	0.5 to 2.5	Depending on desired slip level

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China