

Pyrotek Pyroboard™ S1100 Roller

Category : Ceramic

Material Notes:

Pyroboard™ S1100 is an economical material that is perfect for one time use on new campaigns. Information provided by Pyrotek.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Pyrotek-Pyroboard-S1100-Roller.php

Physical Properties	Metric	English	Comments
Density	0.897 g/cc	0.0324 lb/in³	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	4.00 MPa	580 psi	
Flexural Strength	2.00 MPa	290 psi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1100 °C	2010 °F	
Shrinkage	0.500 %	0.500 %	Surface
	@Temperature 816 °C	@Temperature 1500 °F	
	0.500 %	0.500 %	Thickness
	@Temperature 816 °C	@Temperature 1500 °F	
	2.50 %	2.50 %	Surface
	@Temperature 982 °C	@Temperature 1800 °F	
	4.00 %	4.00 %	Thickness
	@Temperature 982 °C	@Temperature 1800 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China