

Ravago Manufacturing Americas Enviramid™ N1300HL Nylon 66

Category : Polymer , Renewable/Recycled Polymer , Thermoplastic , Nylon , Nylon 66

Material Notes:

Heat Stabilized, Lubricated, Black and made from EnViramid™ Post Consumer Recycled Nylon Information provided by Ravago.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ravago-Manufacturing-Americas-Enviramid-N1300HL-Nylon-66.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.15 g/cc	1.15 g/cc	ASTM D792
Water Absorption	1.2 %	1.2 %	Saturation, Immersed; ASTM D570
Linear Mold Shrinkage, Flow	0.015 - 0.019 cm/cm	0.015 - 0.019 in/in	ASTM D955
	@Thickness 3.17 mm	@Thickness 0.125 in	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	64.8 MPa	9400 psi	ASTM D638
Elongation at Break	10 %	10 %	ASTM D638
Flexural Strength	107 MPa	15500 psi	ASTM D790
Flexural Modulus	2.899 GPa	420.5 ksi	ASTM D790
Izod Impact, Notched	0.481 J/cm	0.900 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	70.0 °C	158 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China