

Reliance Industries Reclair M26500 Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , LLDPE , Linear Low Density Polyethylene (LLDPE), Injection Molded

Material Notes:

High flow Linear Low Density Polyethylene grade. Reclair M26500 is a butene comonomer with optimum levels of antioxidants. Characteristics: narrow molecular weight distribution, excellent processability, excellent flexibility.

Applications: recommended for preparing master batches, injection molding lids, containers, housewares, and general purpose articles.

Information provided by Reliance Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_Reliance-Industries-Reclair-M26500-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.926 g/cc	0.0335 lb/in ³	ASTM D1505
Melt Flow	50 g/10 min @Load 2.16 kg	50 g/10 min @Load 4.76 lb	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	11.5 MPa	1670 psi	ASTM D638
Elongation at Break	600 %	600 %	ASTM D638
Flexural Modulus	0.250 GPa	36.3 ksi	ASTM D790

Thermal Properties	Metric	English	Comments
Softening Point	97.0 °C	207 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China