

## Renegade Materials Corporation RM-3006 Bismaleimide (BMI) Paste Adhesive

Category: Polymer, Thermoset, Filled/Reinforced Thermoset

## **Material Notes:**

Developed using state-of-the-art formulating technologies, RM-3006 BMI Paste Adhesive is a -65°F to 400°F (-54°C to 204°C) service material. RM-3006 was developed for use with Renegade's BMI Prepregs and Infusion Resins as well as other industry standard BMI systems and metals. Information provided by Renegade Materials Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Renegade-Materials-Corporation-RM-3006-Bismaleimide-BMI-Paste-Adhesive.php

| Physical Properties | Metric    | English       | Comments         |
|---------------------|-----------|---------------|------------------|
| Density             | 1.21 g/cc | 0.0437 lb/in³ | Resin; ASTM D790 |

| Mechanical Properties | Metric               | English              | Comments                          |
|-----------------------|----------------------|----------------------|-----------------------------------|
| Hardness, Shore D     | 88                   | 88                   | ASTM D2240                        |
| Compressive Strength  | 0.00758 MPa          | 1.10 psi             | Dry; ASTM D695                    |
|                       | @Temperature 177 °C  | @Temperature 350 °F  |                                   |
|                       | 0.159 MPa            | 23.0 psi             | Dry; ASTM D695                    |
|                       | @Temperature 21.1 °C | @Temperature 70.0 °F |                                   |
| Shear Strength        | 6.10 MPa             | 885 psi              | Lap Shear, Dry; ASTM D1002        |
|                       | @Temperature 177 °C  | @Temperature 350 °F  |                                   |
|                       | 13.77 MPa            | 1997 psi             | Lap Shear, Dry; ASTM D1002<br>O°F |
|                       | @Temperature 21.1 °C | @Temperature 70.0 °F |                                   |

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China