

## **SABIC EPS 552 Expandable Polystyrene**

Category: Polymer, Thermoplastic, Polystyrene (PS), Expanded Polystyrene (EPS)

## **Material Notes:**

Product Description: Standard expanded Polystyrene EPS 552 is manufactured by the suspension polymerization of styrene monomer. The polymerization is generally carried out in a batch process. EPS 552 is an expandable polystyrene grade supplied in free-flowing beads, containing pentane (CFC free) as a foaming agent. It is used for fast cycle shape and block molding applications with good surface finish. Typical Applications: EPS 552 is a standard fast cycle grade used for shape molding with wall thickness greater than 10 mm and for medium-to-high density block molding. Information provided by SABIC.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_SABIC-EPS-552-Expandable-Polystyrene.php

Physical Properties	Metric	English	Comments
Density	0.0170 - 0.0300 g/cc	0.000614 - 0.00108 lb/in <sup>3</sup>	Normal range, one pre-expansion
Bead Size	0.600 - 1.10 mm	0.0236 - 0.0433 in	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China