

SABIC Innovative Plastics LNP COLORCOMP J1000Z PES (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , Polyethersulfone (PES)

Material Notes:

LNP* COLORCOMP* is a compound based on Polyethersulfone resin. Added features include: High Viscosity

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-COLORCOMP-J1000Z-PES-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.37 g/cc	0.0495 lb/in ³	ISO 1183
Water Absorption	1.8 % @Time 86400 sec	1.8 % @Time 24.0 hour	ISO 62-1
Linear Mold Shrinkage, Flow	0.010 cm/cm	0.010 in/in	SABIC Method

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	72.0 MPa	10400 psi	50 mm/min; ISO 527
Tensile Strength, Yield	89.0 MPa	12900 psi	50 mm/min; ISO 527
Elongation at Yield	6.9 %	6.9 %	50 mm/min; ISO 527
Tensile Modulus	2.60 GPa	377 ksi	1 mm/min; ISO 527
Flexural Yield Strength	130 MPa	18900 psi	2 mm/min; ISO 178
Flexural Modulus	2.80 GPa	406 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	6.00 kJ/m ²	2.86 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	NB	NB	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	206 °C	403 °F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China