

SABIC Innovative Plastics LNP LUBRICOMP DFL24 PC (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , Polycarbonate (PC)

Material Notes:

LNP* Lubricomp* DFL24 is a compound based on Polycarbonate resin containing Glass Fiber, PTFE.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-DFL24-PC-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.39 g/cc	0.0502 lb/in ³	ISO 1183
Linear Mold Shrinkage, Flow	0.0020 - 0.0040 cm/cm	0.0020 - 0.0040 in/in	on Tensile Bar; SABIC Method

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	99.0 MPa	14400 psi	5 mm/min; ISO 527
Elongation at Break	3.3 %	3.3 %	5 mm/min; ISO 527
Flexural Strength	135 MPa	19600 psi	2 mm/min; ISO 178
Flexural Modulus	5.80 GPa	841 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	15.0 kJ/m ²	7.14 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	50.0 kJ/m ²	23.8 ft-lb/in ²	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	145 °C	293 °F	Flatw 80*10*4 sp=64mm; ISO 75/Af
Flammability, UL94	V-1 @Thickness 3.00 mm	V-1 @Thickness 0.118 in	UL 94

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China