

SABIC Innovative Plastics LNP LUBRICOMP PFP36 PA 6

Category : Polymer , Thermoplastic , Nylon , Nylon 6

Material Notes:

LNP* LUBRICOMP* PFL36 is a compound based on Nylon 6 resin containing 30% Glass Fiber, 15% PTFE/Silicone. Added features of this grade include: Wear Resistant.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-PFP36-PA-6.php

Physical Properties	Metric	English	Comments
Density	1.22 g/cc	0.0441 lb/in ³	ISO 1183
Linear Mold Shrinkage, Flow	0.012 - 0.014 cm/cm @Time 86400 sec	0.012 - 0.014 in/in @Time 24.0 hour	ISO 294

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	55.0 MPa	7980 psi	ISO 527
Elongation at Break	6.0 - 8.0 %	6.0 - 8.0 %	ISO 527
Tensile Modulus	3.20 GPa	464 ksi	1 mm/min; ISO 527
Flexural Strength	80.0 MPa	11600 psi	ISO 178
Flexural Modulus	3.10 GPa	450 ksi	ISO 178
Izod Impact, Notched (ISO)	8.00 kJ/m ²	3.81 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	100 kJ/m ²	47.6 ft-lb/in ²	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	58.0 Â°C	136 Â°F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China