

S&E Specialty Polymers SE900-6 PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Uncompounded

Material Notes:

Description: PVC weatherable, integral colored, filledApplications: Roof Ditch Molding Skin which meets the Ford WSKM4D689-

A5Information provided by S&E Specialty Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-SE900-6-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	<= 1.35 g/cc	<= 1.35 g/cc	ASTM D792, A

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70 - 80 @Time 15.0 sec	70 - 80 @Time 0.00417 hour	ASTM D2240
Tensile Strength	>= 11.0 MPa	>= 1600 psi	Type IV, 500mm/min; ASTM D638
Elongation at Break	>= 240 %	>= 240 %	Type IV, 500mm/min; ASTM D638
Tear Strength	>= 40.0 kN/m	>= 228 pli	Method B; ISO 34

Descriptive Properties	Value	Comments
Accelerated Weathering	<3.0 DE	after 2000 kj/m ² , SAEJ2527
Cold Flex	-30°C	FLTM BN 102-01

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China