

S&E Specialty Polymers TufTech™ GM-3968 PVC Compound

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Application: A clear, non-toxic, extrusion compound for food contact use. Information provided by S&E Specialty Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-TufTech-GM-3968-PVC-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.19 g/cc	1.19 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65.0	65.0	ASTM D2240
	@Time 15.0 sec	@Time 0.00417 hour	
Tensile Strength	15.5 MPa	2250 psi	ASTM D412
Elongation at Break	450 %	450 %	ASTM D412

Processing Properties	Metric	English	Comments
Processing Temperature	166 - 171 °C	330 - 340 °F	Suggested Stock

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China