

S&E Specialty Polymers XP23-566-1 PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Uncompounded

Material Notes:

Description: PVC weatherable, integral colored, filledApplication: Low gloss lift gate molding compound which meets Chrysler MSDC 543.Information provided by S&E Specialty Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_SE-Specialty-Polymers-XP23-566-1-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	<= 1.30 g/cc	<= 1.30 g/cc	ASTM D792, A

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	34 - 40 @Time 15.0 sec	34 - 40 @Time 0.00417 hour	ASTM D2240
Tensile Strength	>= 15.0 MPa	>= 2180 psi	Type IV, 500mm/min; ASTM D638
Elongation at Break	>= 200 %	>= 200 %	Type IV, 500mm/min; ASTM D638
Tear Strength	>= 45.0 kN/m	>= 257 pli	Method B; ISO 34

Descriptive Properties	Value	Comments
Accelerated Weathering	<3.0 DE	after 2000 kj/m ² , SAEJ2527
Cold Flex	-30°C	GM9503P

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China