

SGL Carbon Group EK 3205 Carbon Graphite

Category : Carbon , Graphite

Material Notes:

Good mechanical strength, good sliding properties, high temperature resistance, high thermal shock resistance, low wettability, high corrosion resistance, high thermal conductivity, high purity, and good electrical conductivity. Typical Applications: High Loaded Seals
Information provided by SGL Carbon Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_SGL-Carbon-Group-EK-3205-Carbon-Graphite.php

Physical Properties	Metric	English	Comments
Density	2.25 g/cc	0.0813 lb/in ³	
Open Porosity	<= 2.5 %	<= 2.5 %	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	115	115	Size/Load - 5/100
Hardness, Shore C	102	102	
Modulus of Elasticity	30.3 GPa	4400 ksi	
Flexural Strength	114 MPa	16500 psi	
Compressive Strength	259 MPa	37500 psi	

Thermal Properties	Metric	English	Comments
CTE, linear	3.96 Åµm/m-Å°C @Temperature 20.0 Å°C	2.20 Åµin/in-Å°F @Temperature 68.0 Å°F	
Thermal Conductivity	20.8 W/m-K	144 BTU-in/hr-ftÅ²-Å°F	
Maximum Service Temperature, Air	399 Å°C	750 Å°F	In oxygen
Maximum Service Temperature, Inert	538 Å°C	1000 Å°F	Reducing Atm.

Descriptive Properties	Value	Comments
Impregnation	Antimony	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China