

SK Chemicals SKYTHANE® 155D R series Polyurethane

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane, TP

Material Notes:

SKYTHANE is a thermoplastic polyurethane elastomer (TPU). Like materials ranging from rubber to plastics, it has excellent physical properties such as anti-abrasion, oil-resistance and mechanical property. It is widely used for automotive parts and various industrial parts. Information provided by SK Chemicals

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-155D-R-series-Polyurethane.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.14 g/cc	1.14 g/cc	ASTM D792
Linear Mold Shrinkage	0.0020 cm/cm	0.0020 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	57	57	ASTM D2240
Tensile Strength, Ultimate	42.2 MPa	6120 psi	ASTM D412
Tensile Strength, Yield	18.6 MPa	2700 psi	ASTM D412
	@Strain 100 %	@Strain 100 %	
	30.4 MPa	4410 psi	ASTM D412
	@Strain 300 %	@Strain 300 %	
Elongation at Break	450 %	450 %	ASTM D412
Resilience	35	35	by vertical rebound; ASTM D2632
Tear Strength	172 kN/m	980 pli	Die C; ASTM D624
Taber Abrasion, mg/1000 Cycles	85	85	H18 Wheel; 1000g load; ASTM D1044

Thermal Properties	Metric	English	Comments
Vicat Softening Point	130 Â°C	266 Â°F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China