

SK Chemicals SKYTHANE® 185A L series Polyurethane

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane, TP

Material Notes:

SKYTHANE is a thermoplastic polyurethane elastomer (TPU). Like materials ranging from rubber to plastics, it has excellent physical properties such as anti-abrasion, oil-resistance and mechanical property. It is widely used for automotive parts and various industrial parts. Information provided by SK Chemicals

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-185A-L-series-Polyurethane.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.18 g/cc	1.18 g/cc	ASTM D792
Linear Mold Shrinkage	0.0045 cm/cm	0.0045 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85	85	ASTM D2240
Hardness, Shore D	35	35	ASTM D2240
Tensile Strength, Ultimate	34.3 MPa	4980 psi	ASTM D412
Tensile Strength, Yield	5.39 MPa @Strain 100 %	782 psi @Strain 100 %	ASTM D412
	12.7 MPa @Strain 300 %	1850 psi @Strain 300 %	ASTM D412
Elongation at Break	600 %	600 %	ASTM D412
Resilience	40	40	by vertical rebound; ASTM D2632
Tear Strength	98.1 kN/m	560 pli	Die C; ASTM D624
Taber Abrasion, mg/1000 Cycles	20	20	H18 Wheel; 1000g load; ASTM D1044

Thermal Properties	Metric	English	Comments
Vicat Softening Point	90.0 Â°C	194 Â°F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China