

SK Chemicals SKYTHANE® 398A S series Polyurethane

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane, TP

Material Notes:

SKYTHANE is a thermoplastic polyurethane elastomer (TPU). Like materials ranging from rubber to plastics, it has excellent physical properties such as anti-abrasion, oil-resistance and mechanical property. It is widely used for automotive parts and various industrial parts. Information provided by SK Chemicals

Order this product through the following link:

http://www.lookpolymers.com/polymer_SK-Chemicals-SKYTHANE-398A-S-series-Polyurethane.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.22 g/cc	1.22 g/cc	ASTM D792
Linear Mold Shrinkage	0.0040 cm/cm	0.0040 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	98	98	ASTM D2240
Hardness, Shore D	55	55	ASTM D2240
Tensile Strength, Ultimate	38.2 MPa	5550 psi	ASTM D412
Tensile Strength, Yield	17.7 MPa	2560 psi	ASTM D412
	@Strain 100 %	@Strain 100 %	
	31.9 MPa	4620 psi	ASTM D412
	@Strain 300 %	@Strain 300 %	
Elongation at Break	400 %	400 %	ASTM D412
Resilience	31	31	by vertical rebound; ASTM D2632
Tear Strength	167 kN/m	952 pli	Die C; ASTM D624
Taber Abrasion, mg/1000 Cycles	75	75	H18 Wheel; 1000g load; ASTM D1044

Thermal Properties	Metric	English	Comments
Vicat Softening Point	116 °C	241 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China