

SMAC CABLE® 2515S-30-10 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Clips: Stainless steel Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2515S-30-10-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	18.0 daN	18.2 mm, 45Â° down and out
	26.3 daN	13.5 mm, left and right
	33.0 daN	14.3 mm, up and down
	36.0 daN	17.2 mm, down
	75.0 daN	7.0 mm, up
F, Max Static	11.0 daN	6.0 mm, 45Â° down and out
	15.0 daN	4.4 mm, down
	15.0 daN	1.9 mm, up
	8.0 daN	5.7 mm, up and down
	8.0 daN	5.6 mm, left and right
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China