

SMAC CABLE® 25235-30-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-25235-30-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1330 daN	43.0 mm, down
	1710 daN	25.0 mm, up
	600.0 daN	32.5 mm, up and down
	778.0 daN	40.0 mm, left and right
	810.0 daN	51.0 mm, 45Â° down and out
F, Max Static	225.0 daN	11.0 mm, up and down
	225.0 daN	13.8 mm, left and right
	350.0 daN	12.5 mm, 45Â° down and out
	450.0 daN	10.0 mm, down
	450.0 daN	8.3 mm, up
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China