

SMAC CABLE® 2525S-10-08 Damping Material

Category : Other Engineering Material

Material Notes:

The SMAC CABLE® wire rope isolators are entirely metallic and possess multi-axis characteristics. They are well adapted for the isolation of materials exposed to shock and vibration in harsh environment. Descriptions Bars: Aluminum alloy Screws: Inox A2 Threaded insert: Stainless steel Standard treatment: SurTec 650 Information provided by SMAC MontBlac Groupe Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_SMAC-CABLE-2525S-10-08-Damping-Material.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 - 300 Â°C	356 - 572 Â°F	

Descriptive Properties	Value	Comments
Damping Factor	0.1 - 0.2	
F, Max Dynamic	1030 daN	36.0 mm, left and right
	1750 daN	57.0 mm, 45Â° down and out
	2875 daN	55.0 mm, down
	3375 daN	29.0 mm, up
	800.0 daN	24.4 mm, up and down
F, Max Static	1000 daN	9.0 mm, down
	1000 daN	8.8 mm, up
	300.0 daN	6.0 mm, up and down
	300.0 daN	5.8 mm, left and right
	750.0 daN	11.5 mm, 45Â° down and out
Transmissibility at resonance	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China