

SPS Guang Zhou SAMATê,ç EP 5001C(f1) Flame-retarded Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Flame Retardant

Material Notes:

Characteristic: Good flame retardance, non-halogen, high flow properties, high rigidity, high heat resistance, meets the requirements of RoHs and PaHs, excellent UV resistance
Applications: X'mas decorative product, E/E appliance
Information Provided by SPS (Guang Zhou) Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SPS-Guang-Zhou-SAMAT-EP-5001Cf1-Flame-retarded-Polypropylene.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.06 g/cc	1.06 g/cc	ASTM D792
Melt Flow	10 g/10 min	10 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	25.0 MPa	3630 psi	ASTM D638
Flexural Strength	40.0 MPa	5800 psi	
Flexural Modulus	2.00 GPa	290 ksi	
Izod Impact, Notched	0.220 J/cm	0.412 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	125 Â°C	257 Â°F	ASTM D648

Descriptive Properties	Value	Comments
Flammability	UL1694-SC-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China