

SSAB Tunnplat Aluzink 280A YP High-strength Metal-coated Steel

Category : Metal , Ferrous Metal , Alloy Steel , Low Alloy Steel

Material Notes:

High-strength Metal-coated SteelComments: Aluzink YP - HSLA steel (aluminum-zinc coated sheet). Property values are for thicknesses 0.4 - 2.0 mm. Iron content is approximate - exact composition is not reported by the manufacturer.Data provided by SSAB Tunnplat.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SSAB-Tunnplat-Aluzink-280A-YP-High-strength-Metal-coated-Steel.php

Physical Properties	Metric	English	Comments
Density	7.87 g/cc	0.284 lb/in ³	Estimated by MatWeb

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	350 - 420 MPa	50800 - 60900 psi	
Tensile Strength, Yield	280 - 350 MPa @Strain 0.200 %	40600 - 50800 psi @Strain 0.200 %	
Elongation at Break	>= 24 %	>= 24 %	A₈₀; For thicknesses < 0.70 mm values 2% lower apply
Bend Radius, Minimum	>= 1.0 t	>= 1.0 t	90° bending; avoid bending and rebending

Component Elements Properties	Metric	English	Comments
Iron, Fe	98 %	98 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China