

SSAB Tunnplat Aluzink B500A Metal-coated Mild Steel

Category : Metal , Ferrous Metal , Carbon Steel , Low Carbon Steel

Material Notes:

Metal-coated Mild SteelComments: Aluzink - Aluminum-zinc coated sheet. Property values are for thicknesses 0.4 - 2.00 mm. Iron content is approximate - exact composition is not reported by the manufacturer.Data provided by SSAB Tunnplat.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SSAB-Tunnplat-Aluzink-B500A-Metal-coated-Mild-Steel.php

Physical Properties	Metric	English	Comments
Density	7.87 g/cc	0.284 lb/in ³	Estimated by MatWeb

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	<= 500 MPa	<= 72500 psi	
Bend Radius, Minimum	>= 1.0 t	>= 1.0 t	90° bending; avoid bending and rebending

Component Elements Properties	Metric	English	Comments
Iron, Fe	98 %	98 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China