

Saint-Gobain CHR® 2283-2 Extruded PTFE Film Backing Acrylic Adhesive Pressure Sensitive Tape

Category: Polymer, Adhesive, Tape, Thermoplastic, Acrylic (PMMA)

Material Notes:

Description: PTFE films provide a conformable release surface and exhibit a remarkably low coefficient of friction and non-stick properties. PTFE films have high temperature resistance and are virtually unaffected by all chemicals. At elevated temperatures, PTFE film still retains excellent tensile strength. Service temperatures range from -100°F to +500°F (-73°C to 260°C). This tape uses an acrylic adhesive system. Acrylic adhesves perform in continuous operating temperatures from -40°F to +375°F (-40°C to +188°C). Benefits include exceptional solvent resistance, excellent adhesion to metal, superior weathering and aging characteristics. Acrylics have an excellent shelf life, and when exposed to elevated temperatures, their ability to wet-out improves thus increasing both adhesion and tack properties. All data based on a 0.004 inch test sample. (Thickness given is for both backing and adhesive. Backing thickness is .002 inches.) Information provided by Saint Gobain Performance Products.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Saint-Gobain-CHR-2283-2-Extruded-PTFE-Film-Backing-Acrylic-Adhesive-Pressure-Sensitive-Tape.php

| Mechanical Properties | Metric | English | Comments |
|-----------------------|-----------|----------|-----------------------|
| Elongation at Break | 150 % | 150 % | |
| Tear Strength | 5.26 kN/m | 30.0 pli | Initial Tear Strength |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|----------|
| Maximum Service Temperature, Air | 177 °C | 350 °F | |
| Minimum Service Temperature, Air | -40.0 °C | -40.0 °F | |

| Electrical Properties | Metric | English | Comments |
|-----------------------|------------|------------|----------|
| Dielectric Strength | 98.4 kV/mm | 2500 kV/in | |
| Dielectric Breakdown | 10000 V | 10000 V | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Color | Rust | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China