

Shandong Dongyue Polymer DF-21A PTFE Presintered Resin

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

Material Notes:

Usage: The presintered resin is suitable for continuously extruding of all types, pushing and pressing PTFE rod, tube and special shape. Packing: PTFE is packed in double layer PVC bags inside and in hard circular barrels outside. Storage: PTFE should be stored in a clean, dry warehouse to protect from dust, moisture, etc. Transportation: The products are transported according to non-dangerous products. Heat, moisture, freezing and strong shock should be avoided during transportation. Over-bumpiness and compression is apt to make the resin bind together. Conformable with Q/DYG 007-2004 Information provided by Shandong Dongyue Polymer Material Co., Ltd

Order this product through the following link:

http://www.lookpolymers.com/polymer_Shandong-Dongyue-Polymer-DF-21A-PTFE-Presintered-Resin.php

Physical Properties	Metric	English	Comments
Bulk Density	0.500 - 0.800 g/cc	0.0181 - 0.0289 lb/in ³	
Particle Size	500 - 900 Åµm	500 - 900 Åµm	

Thermal Properties	Metric	English	Comments
Melting Point	322 - 332 Å°C	612 - 630 Å°F	

Descriptive Properties	Value	Comments
Machining Method	Ram extrusion	
Powder Flow (g/min)	450	
Smoothness & Cleanliness	First Grade: Clean and white surface, no metal impurity, the impurity quantity from 1-3 mm doesn't exceed two	
	Qualified: Clean and white surface, no metal impurity, the impurity quantity from 1-3 mm doesn't exceed four	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China