

Shin-Etsu Silicones KE-9610U Silicone Elastomer

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Silicone , Silicone Rubber

Material Notes:

KE9610 U is one of a series of easy processing, general purpose silicone rubber base with low volatile content. It can be used in a variety of applications requiring finishing by molding, extruding or calendering. Product Features: Rubber contacts. Food packing. Industrial packing. Diaphragms. Information Provided by Shin-Etsu Silicones of America, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Shin-Etsu-Silicones-KE-9610U-Silicone-Elastomer.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.22 g/cc	1.22 g/cc	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	61	61	
Tensile Strength at Break	8.701 MPa	1262 psi	
Elongation at Break	280 %	280 %	
Tear Strength	11.7 kN/m	67.0 pli	Die B
Compression Set	8.0 % @Temperature 149 Â°C, Time 79200 sec	8.0 % @Temperature 300 Â°F, Time 22.0 hour	

Processing Properties	Metric	English	Comments
Cure Time	240 min @Temperature 200 Â°C	4.00 hour @Temperature 392 Â°F	Post

Descriptive Properties	Value	Comments
Cure Agent	DBPH	
Cure Type	Post Cure	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China