

## **Sibur Phenoplast**

Category: Polymer, Thermoplastic, Polyethylene (PE), LDPE

**Material Notes:** 

For production by direct pressing.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Sibur-Phenoplast.php

Physical Properties	Metric	English	Comments
Density	<= 1.50 g/cc	<= 0.0542 lb/in³	
Linear Mold Shrinkage	0.0020 - 0.0050 cm/cm	0.0020 - 0.0050 in/in	
Collected Volatile Condensable Material	<= 9.0 %	<= 9.0 %	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 79.0 MPa	>= 11500 psi	Bending
Charpy Impact Unnotched	>= 0.880 J/cm²	>= 4.19 ft-lb/in²	

Thermal Properties	Metric	English	Comments	
Deflection Temperature at 1.8 MPa (264 psi)	>= 150 °C	>= 302 °F		

Electrical Properties	Metric	English	Comments
Volume Resistivity	>= 1.00e+9 ohm-cm	>= 1.00e+9 ohm-cm	

Descriptive Properties	Value	Comments
Electric Density, KW/mm	>6	
Flow, mm	40-140	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China