

Sika Industry SikaTack UltraFast Fast Cure One Part Polyurethane Adhesive

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS , Thermoset Polyurethane, Adhesive

Material Notes:

Sika UltraFast SikaTack Fast Cure One Part Polyurethane Adhesive This revolutionary product uses heat instead of moisture to "pre-cure" the adhesive. The product is heated before applications using a SikaTack oven for extremely fast installation of glass to metal or metal to metal. 1 mm Cut-Off, Excellent non-sag, available in black. Cure Type: Heat and Moisture

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sika-Industry-SikaTack-UltraFast-Fast-Cure-One-Part-Polyurethane-Adhesive.php

Physical Properties	Metric	English	Comments
Density	1.15 g/cc	0.0416 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60 - 70	60 - 70	
Tensile Strength, Ultimate	5.52 - 6.21 MPa	800 - 900 psi	
Elongation at Break	500 - 600 %	500 - 600 %	
Adhesive Bond Strength	4.14 - 4.83 MPa	600 - 700 psi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.3 Â°C	200 Â°F	
Minimum Service Temperature, Air	-40.0 Â°C	-40.0 Â°F	

Processing Properties	Metric	English	Comments
Cure Time	10.0 - 15.0 min	0.167 - 0.250 hour	Tack-free
	1440 min	24.0 hour	Value given per 3/16 inches
Shelf Life	9.00 Month	9.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China