

Silon Tabond 2003 Adhesive Resin

Category : Polymer , Adhesive , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

Material Notes:

TABOND 2003 is a ethylene-octene copolymer modified with maleic anhydride functional groups.Characteristics: â€¢ Strong adhesion to aminosilane treated glass, Nylon, EVOH, PET, PBT, PC, aluminium, copper, brass and steel â€¢ Adhesion durability â€¢ Polyolefin like properties and processingInformation provided by Silon

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silon-Tabond-2003-Adhesive-Resin.php

Physical Properties	Metric	English	Comments
Density	0.880 g/cc	0.0318 lb/in ³	
Melt Flow	1.5 g/10 min @Load 2.16 kg, Temperature 190 Â°C	1.5 g/10 min @Load 4.76 lb, Temperature 374 Â°F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	71.6	71.6	15s

Thermal Properties	Metric	English	Comments
Melting Point	65.0 Â°C	149 Â°F	DSC

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China